

# Architectural Door Accessories

ASSA ABLOY


## Pemko Product Reference Tech-Spec

The global leader in  
door opening solutions

### 217\_V

#### Door Bottom

Example: 217 | A | V | 36  
Profile# Finish Eco-V® Length



**TYPE:** Door Shoe

**MATERIAL:** 6063-T6 Aluminum Alloy and Temper Retainer

**FINISH:** A (Mill Finish), BDG (Bright Dip Gold Anodized), D (Dark Anodized), G (Gold Anodized), PW (Painted White), SN (Satin Nickel Anodized)

**LENGTHS:** Up to 185"

**WIDTH:** 1-23/32" (43.653 mm)

**HEIGHT:** Overall: 1-7/16" (36.512 mm), Underneath door: 1/2" (12.7 mm)

**WEIGHT:** Estimated per foot: 0.425 lbs

**ANSI NUMBER:** R3G414

**LEAD TIME:** 4 working days or less

**AVAILABLE:** Shipped from Pemko's Memphis, Ventura, Vancouver, and Toronto locations

**WARRANTY:** 5 Years from purchase date

**CROSS REFERENCE:** DraftSeal: DS217; Hager: 779S, 779V; NGP: 26; Reese: DB594, Zero/Allegion: 111

#### **INSTRUCTIONS, CAD DRAWINGS, PROFILE DRAWINGS and CUT SHEET**

Available upon request and on website

#### PRODUCT TESTING:

- **Smoke Tested** – Tested to UL 1784 and meets the requirements of NFPA 105-2013 for smoke leakage in an opening; allows no more than 3.0 cfm per square foot at 0.10" water column (about 75 Pa).
- **Fire Rated** – Tested to UL10B Standard Fire Tests and UL10C Positive Pressure Fire Tests of Door Assemblies
- **BHMA Certified** – Tested for performance with regards to the requirements in:
  - ANSI/BHMA A156.22 – Door Gasketing and Edge Seal Systems
- **Prop 65** – This product contains a chemical known to the state of California to cause cancer:
  - Polyvinyl Chloride (PVC) - Eco-V

#### Product Test Ratings:



See Product Testing  
section for more  
information.