## **Product**

## 725 Series

Door & Drawer Locks for Small Format IC Cores



725MD-DR-RH Mortise, Deadbolt, Right-hand

725RD-DR-LH

Rim. Deadbolt.

Left-hand



725ML-DW-IH Mortise, Latchbolt, Inverted-hand

725 Series lock

Best-style small

changeable cores

bodies accept

format inter-

(core not in-

cluded)



Rim. Latchbolt. Vertical-hand



725RL-DW-VH



Includes plastic actuator to functionally test lock without core

- Surface or mortise mount
- Latch or deadbolt
- Door (Right-hand or Left-hand)
- Drawer (Vertical or Inverted)
- Includes matching strike plate



### 725 SERIES

#### Door & Drawer Locks for Small Format IC Cores

# OLYMPUS LOCK, INC.

#### **General Specifications**

#### 725 Series Door & Drawer Locks

Body: Zinc die cast cylinder housing, stamped steel back plate and steel case Barrel diameter: 1-1/8"

Max. material thickness: 1-1/16" Compatability: Retrofits Best 5L Series Finish: US26 (polished chrome), US26D (satin chrome), US3 (bright brass), US4 (satin brass) Cylinder: not included, accepts standard small format format IC cores as manufactured by Best, Arrow, Falcon, Schlage or other compatible small format IC core manufacturers

Keying: n/a


#### Accessories


#### Includes:


- 725-PA plastic actuator
- 725-1 spacer for 6 pin cores
- 725-SP series matching strike plate


#### **Additional Functions**


- 725ML/725RL reverse latch available for DW-VH functions - use reverse latch for in-swinging door applications
- 725MD/725RD key retaining function available for DW-VH or DW-IH applications












#### **725RD/725RL Series Dimensions**



#### **725MD/725ML Series Dimensions**

725RD

