

IMPORTED FIRE SAFES

The economical range of our **IMPORTED RESIDENTIAL FIRE SAFES (ELECTRONIC and COMBO)** is the answer's to today's high incidence of residential fires. Our Fire Safes also provide burglary protection making them ideal for home and light commercial applications. Our FS2215 **IMPORTED COMMERCIAL FIRE SAFE** is larger and perfect for both commercial and residential applications.







IMPORTED RESIDENTIAL FIRE SAFES (ELECTRONIC)

FEATURES: EST712, EST914 / EST149 / EST1814:

- U.L. Listed 350°F, 1-Hour fire rating.
- Side boltwork mechanism incorporating two 1/2" diameter steel deadbolts prevent door removal during a forced entry attempt. (EST1814 model: 1 x 4-1/2" rectangular steel deadbolts).
- New State-of-the-art DL5000 electronic lock with a large 3 ¾" touch screen LCD input display allows smooth and easy operation.
- Mode altering display changes from orange in standby mode to bright blue in the open position.
- Accepts (2) user codes and can show open door records for the past 14 entries.
- LCD touch screen display shows lowbattery indicator, time, date and keypad.
- Emergency key-lock override system with two (2) keys, power override battery box, built-in spy-proof function and motion detector alert.

- One (1) drawer shelf and one (1) internal anchor hole with hardware.
- Impressive 1/2" thick door with attractive two-toned sage finish (EST1814 model: 5/8" thickness).
- Four (4) rubber feet. (EST1814 model has four rolling casters).

IMPORTED RESIDENTIAL FIRE SAFES (COMBO) FEATURES:

FS914 / FS149:

- U.L. Listed 350°F 1-Hour fire rating.
- Models FS914 and FS149 have one

 (1) internal anchor hole and hardware, four (4) rubber feet and one (1) drawer shelf (except model FS712 that has a removable shelf).
- Key operated side-locking mechanism incorporating two chromed locking bolts.
- Two deadbolts prevent door removal if hinges are removed during a forced entry attempt.
- · Attractive two-toned sage finish.

FS2215 IMPORTED COMMERCIAL FIRE SAFE

FEATURES:

- U.L. Listed 350°F 1-Hour fire rating.
- Model FS2215 offers a Group 2 combination lock with a Spyproof dial and ring, one (1) key-lock drawer, one (1) adjustable shelf, four (4) rolling casters for ease of movement and additional chrome "L" handle.
- Automatic relocking device triggered by force entry attempt.
- Handle operated side, top and bottom locking mechanism incorporating four steel chromed locking bolts.
- Two steel deadbolts prevent door removal if hinges are removed during a forced entry attempt.
- Ball bearing hinges for ease of operation.
- Attractive two-toned sage finish.



OPTIONAL LED LIGHT KIT WITH MOTION SENSOR AVAILABLE FOR ALL MODELS. SEE PAGE 28 FOR DETAILS.

Residential Fire Safes (Electronic and Combo)

Model	Inside Dim H x W x D	Outside Dim* H x W x D	Clear Door	Cu. In.	Wt
EST712	7 x 11¼ x 8-3/8	11¾ x 16½ x 13¾	7 x 11¼	660	70
EST914	8-7/16 x 14 x 10½	13½ x 19-1/8 x 15¾	8-7/16 x 14	1,107	96
EST149	14-1/8 x 8¼ x 10¾	19-1/8 x 13½ x 15-11/16	14-1/8 x 81/4	1,258	96
EST1814	18¼ x 13-1/8 x 12-3/8	23-5/8 x 18-7/8 x 18-7/8	18¼ x 13-1/8	2,920	187
FS914	8-3/8 x 14 x 10¾	13½ x 19-1/8 x 15¾	8-3/8 x 141/4	1,189	96
FS149	14-1/8 x 8¼ x 10¾	19-1/8 x 13½ x 15-11/16	14-1/8 x 81/4	1,258	96

Residential Fire Safes (Electronic and Combo)

Model	Inside Dim H x W x D	Outside Dim* H x W x D	Clear Door	Cu. In.	Wt
FS2215	17¾ x 13-7/8 x 13-3/8	30-3/8 x 19¾ x 19-3/8	17¾ x 13-7/8	2,786	225

*Add 2" for handle, dial and hinge projection.

Model FS2215 has one key-lock drawer and one adjustable shelf.

Outside height includes casters on model FS2215.

Above dimensions have been converted from metric measurements. Please allow +1/4" to 1/4" variation for both outer and inner dimensions listed.